



SDS65K8-01

FEATURES

Panel Type	65" TFT UHD Panel
Display Size (Inch)	65"
Number of Pixels	3840 x 2160
Active Display Area (mm)	1428.48(H) x 803.52(V)
Aspect Ratio	16:9
Refresh Rate	60 Hz
Contrast Ratio (type)	1200:1 Static / 50 000:1 Dynamic
Brightness (cd/m2)	500
Peak White Luminance Ratio	95%
Response Time	6 ms
Viewing Angle	178/178
Colors	1.07 Billion Colors
Operating Time	24/7

POWER AND ECO DESIGN

Power Supply	100 - 240 V ~ 50/60 Hz
Power Consumption	232 W
Power Consumption Stand-by	0.4 W
Lead Presence	Yes
Mercury	0 mg
Energy Class	G

AUDIO

Loud Speaker	2 x 10 W
--------------	----------

DIMENSIONS AND WEIGHT

Outline Dimensions	1456.5 x 831.5 x 61.8 mm
Weight - Product	17.3 kg
Package Dimensions	1590 x 160 x 985 mm
Weight - Package	22.4 kg
Vesa Hole	400 x 400 mm

STANDARD CONFIGURATION

HDMI	1 x HDMI 1 ARC/CEC, 1 x HDMI 2, 1 x HDMI 3 MHL HDMI 2.0/1.4b / HDCP 2.2/1.4 MHL 3.0/2.1 Compatible 480i/576i, 480p/576p, 720p/1080i/1080p, 2160i/2160p
USB	2 x USB 2.0 HOST USB Play list mode, USB Simple mode USB Auto play mode Video, USB Auto play mode Photo, USB Auto play mode Video/Photo
Coaxial	1 x Coaxial Out 75Ω, 0.5Vpp, PCM Audio

ENVIRONMENTAL

Operating Temperature	0°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Operating Ambient Humidity	10% ~ 80% RH
Storage Humidity	10% ~ 90% RH

ACCESSORIES

Included	Remote Control, Power Cable
----------	-----------------------------