



SDST50K8-01

FEATURES

Panel Type	50" TFT UHD Panel
Display Size (Inch)	50"
Number of Pixels	3840 x 2160
Active Display Area (mm)	1095.84(H) x 616.41(V)
Aspect Ratio	16:9
Refresh Rate	60 Hz
Contrast Ratio (type)	1200:1 Static / 50 000:1 Dynamic
Brightness (cd/m2)	300
Peak White Luminance Ratio	95%
Response Time	6 ms
Viewing Angle	178/178
Colors	1.07 Billion Colors
Operating Time	24/7

TOUCH

Touch Technology	Infrared
Touch Points	10 Points
Glass	3 mm Tempered Glass

POWER AND ECO DESIGN

Power Supply	100 - 240 V ~ 50/60 Hz
Power Consumption	90 W
Power Consumption Stand-by	0.4 W
Lead Presence	Yes
Mercury	0 mg
Energy Class	G

AUDIO

Loud Speaker 2 x 6 W

DIMENSIONS AND WEIGHT

Outline Dimensions 1135.24 x 666 x 59 mm

Weight - Product 21 kg

Package Dimensions 1270 x 150 x 780 mm

Weight - Package 26 kg

VESA 400 x 400 mm

STANDARD CONFIGURATION

HDMI 1 x HDMI 1 ARC/CEC, 1 x HDMI 2, 1 x HDMI 3 MHL
HDMI 2.0/1.4b / HDCP 2.2/1.4 MHL 3.0/2.1 Compatible
480i/576i, 480p/576p, 720p/1080i/1080p, 2160i/2160p

USB 2 x USB 2.0 HOST
USB Play list mode, USB Simple mode
USB Auto play mode Video, USB Auto play mode Photo, USB Auto play mode Video/Photo

Coaxial 1 x Coaxial Out
75Ω, 0.5Vpp, PCM Audio

ENVIRONMENTAL

Operating Temperature 0°C ~ 40°C

Storage Temperature -20°C ~ 60°C

Operating Ambient Humidity 10% ~ 80% RH

Storage Humidity 10% ~ 90% RH

ACCESSORIES

Included Remote Control, Power Cable, USB Touch Cable, Special Pen