



## UMX-49K8-01

### FEATURES

Panel Type	49" TFT FHD Panel
Display Size (Inch)	49"
Number of Pixels	1920 x 1080
Active Display Area (mm)	1073.8(H) x 604(V)
Aspect Ratio	16:9
Refresh Rate	60 Hz
Contrast Ratio (type)	1000:1 Static / 50 000:1 Dynamic
Brightness (cd/m2)	450
Peak White Luminance Ratio	95%
Response Time	8 ms
Viewing Angle	178/178
Colors	1.07 Billion Colors
Operating Time	24/7

### POWER AND ECO DESIGN

Power Supply	100 - 240 V ~ 50/60 Hz
Power Consumption	120 W
Power Consumption Stand-by	0.4 W
Lead Presence	Yes
Mercury	0 mg
Energy Class	G

## DIMENSIONS AND WEIGHT

The Package Contains 2 pcs UMX-49K8-01

Outline Dimension	1078 x 608 x 83 mm
Weight - Product	20.5 kg
Package Dimension	1290 x 330 x 770 mm
Weight - Package	46 kg
VESA	600 x 300 mm

## BEZEL/EDGES

Left	2 mm
Right	1.5 mm
Top	2 mm
Bottom	1.5 mm

## STANDARD CONFIGURATION

HDMI (2.0)	1
DVI	1
VGA	1
DP	1
AV	1
USB (Upgrade Software)	1
CVBS	1
RS232 IN	1
RS232 OUT	2

## ENVIRONMENTAL

Operating Temperature	0°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Operating Ambient Humidity	10% ~ 80% RH
Storage Humidity	10% ~ 90% RH

## ACCESSORIES

Included	Remote Control, IR Cable, RJ45 Cable, RS232 Cable, Power Cable
----------	----------------------------------------------------------------