



UMX-55K8-01

FEATURES

Panel Type	55" TFT FHD Panel
Display Size (Inch)	55"
Number of Pixels	1920 x 1080
Active Display Area (mm)	1209.6(H) x 680.4(V)
Aspect Ratio	16:9
Refresh Rate	60 Hz
Contrast Ratio (type)	1000:1 Static / 50 000:1 Dynamic
Brightness (cd/m2)	500
Peak White Luminance Ratio	95%
Response Time	6 ms
Viewing Angle	178/178
Colors	1.07 Billion Colors
Operating Time	24/7

POWER AND ECO DESIGN

Power Supply	100 - 240 V ~ 50/60 Hz
Power Consumption	120 W
Power Consumption Stand-by	0.4 W
Lead Presence	Yes
Mercury	0 mg
Energy Class	G

DIMENSIONS AND WEIGHT

The Package Contains 2 pcs UMX-55K8-01

Outline Dimensions	1213.5 x 684.3 x 79.9 mm
Weight - Product	15 kg
Package Dimensions	1360 x 265 x 870 mm
Weight - Package	32.5 kg
VESA	600 x 400 mm

BEZEL/EDGES

Left	2 mm
Right	1.5 mm
Top	2 mm
Bottom	1.5 mm

STANDARD CONFIGURATION

HDMI (2.0)	1
DVI	1
VGA	1
DP	1
AV	1
USB (Upgrade Software)	1
CVBS	1
RS232 IN	1
RS232 OUT	2

ENVIRONMENTAL

Operating Temperature	0°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Operating Ambient Humidity	10% ~ 80% RH
Storage Humidity	10% ~ 90% RH

ACCESSORIES

Included	Remote Control, IR Cable, RJ45 Cable, RS232 Cable, Power Cable
----------	--