



UMX-65K8-01

FEATURES

Panel Type	65" TFT UHD Panel
Display Size (Inch)	65"
Number of Pixels	3840 x 2160
Active Display Area (mm)	1428.48(H) x 803.52(V)
Aspect Ratio	16:9
Refresh Rate	60 Hz
Contrast Ratio (type)	1000:1 Static / 50 000:1 Dynamic
Brightness (cd/m2)	500
Peak White Luminance Ratio	95%
Response Time	6 ms
Viewing Angle	178/178
Colors	1.07 Billion Colors
Operating Time	24/7

POWER AND ECO DESIGN

Power Supply	100 - 240 V ~ 50/60 Hz
Power Consumption	265 W
Power Consumption Stand-by	0.4 W
Lead Presence	Yes
Mercury	0 mg
Energy Class	G

DIMENSIONS AND WEIGHT

The Package Contains 2 pcs UMX-65K8-01

Outline Dimensions	1432.58 x 807.62 x 117.9 mm
Weight - Product	26 kg
Package Dimensions	1530 x 330 x 910 mm
Weight - Package	55.9 kg
VESA	709 x 510 mm

BEZEL/EDGES

Left	2 mm
Right	1.5 mm
Top	2 mm
Bottom	1.5 mm

STANDARD CONFIGURATION

HDMI (2.0)	1
DVI	1
VGA	1
DP	1
AV	1
USB (Upgrade Software)	1
CVBS	1
RS232 IN	1
RS232 OUT	2

ENVIRONMENTAL

Operating Temperature	0°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Operating Ambient Humidity	10% ~ 80% RH
Storage Humidity	10% ~ 90% RH

ACCESSORIES

Included	Remote Control, IR Cable, RJ45 Cable, RS232 Cable, Power Cable
----------	----------------------------------------------------------------